

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Currently Amended) A track cover, comprising:
- a. an elongated body capable of <u>at least</u> partially covering the top and opposite side sections and the side opening of a track on a track vehicle, said elongated body including a <u>perimeter edge and a lower edge</u>;
- b. a durable mat <u>including an inside edge</u> attached to said lower edge on said elongated body; and,
- c. a plurality of elastic straps used to attach <u>and hold</u> said elongated body over the top, <u>the side sections</u>, and side <u>surfaces opening</u> of the track on the track vehicle when <u>the mat is longitudinally aligned over the bed of a transporting vehicle and the track of a track vehicle is longitudinally aligned over said mat. <u>said elongated body is placed over the track.</u></u>
- 2. (Currently Amended) The track cover, as recited in Claim 1, further including a protective belt attached to said perimeter edge of said elongated body to which said elastic straps are attached to hold said elongated body over the track of a track vehicle.
- 3. (Previously Amended) The track cover, as recited in Claim 2, further including at least one pleat formed on said elongated body that enable said elongated body to conform in size and shape to the track on a track vehicle.

1.	4. (Original) The track cover, as recited in Claim 1, wherein said elongated body includes
2	an upper section that partially extends over the top surface of the track on a track vehicle.
3	
4	5. (Original) The track cover, as recited in Claim 1, wherein said elongated body is made of
5	vinyl.
6	
7	6. (Original) The track cover, as recited in Claim 5, wherein said vinyl is 18 oz.
8	
9	7. (Previously Amended) The track cover, as recited in Claim 2, further including a cut out
10	area formed on the lower edge of said elongated body in which the perimeter edge of said ma
11	extends.
12	
13	8. (Original) The track cover, as recited in Claim 1, wherein said mat is made of rubber.
14	
15	9. (Previously Amended) The track cover, as recited in Claim 1, further including a plurality
16	of D-rings attached to said perimeter edge of said elongated body that connect to said elastic
17	straps to hold said elongated body over the track.
18	
19	10. (Original) The track cover, as recited in Claim 1, wherein said elongated body includes
20	an elevated center axis that enables said elongated body to be used on a track with an
21	elevated center axis.
22	
1	

11. (Withdrawn) The track cover, as recited in Claim 1, further including slots formed on

1	15. (Original) The track cover, as recited in Claim 12, wherein said elongated body is made
2	of vinyl.
3	
4	16. (Previously Amended) The track cover, as recited in Claim 12, wherein said elongated
5	body is made of vinyl.
6	
7	17. (Previously Amended) The track cover, as recited in Claim 12, further including a cut
8	out area formed on said lower edge of said elongated body, in which the perimeter edge of
9	said mat extends.
10	
11	18. (Original) The track cover, as recited in Claim 12, wherein said mat is made of rubber.
12	
13	19. (Original) The track cover, as recited in Claim 12, wherein said elongated body includes
14	an elevated center axis that enables said elongated body to be used on a track with an
15	elevated center axis.
16	
17	20. (Withdrawn- Currently Amended) A method for preventing debris from the tracks on a
18	track vehicle from falling onto the roadway when transporting the track vehicle on a trailer or
19	the bed of a transport vehicle comprising the following steps:
20	a. selecting at least one track cover that includes an elongated body that fits over
21	the track on a track vehicle, said elongated body being sufficient in size and shape to over
22	cover the side opening on the track, said elongated body including a longitudinally aligned
23	mat attached to a lower perimeter edge;

1	D.
2	said mat is lo
3	upon by the t
4	of a transpor
5	c.
6	track located
7	d.
8	elastic straps
9	
10	
11	
12	
13	
14	
15	
16	
١7	
18	
19	
20	
21	
22	
,,	

- b. positioning the track cover on the trailer or bed of a transport vehicle so that said mat is longitudinally aligned on the trailer or bed of a transport vehicle and by driven upon by the track of a track vehicle when the track vehicle is transported on the trailer or bed of a transport vehicle, and said elongated body being disposed over the side of the track;
- c. extending said elongated body over the side opening and the top surface of the track located on said mat; and,
- d. securely attaching said elongated body over the track of the track vehicle <u>using</u> elastic straps.